

# 12tクレーン付きトラック

## MAIN SPECIFICATION OF CRANE TRUCK

New Cab	Model	HFC5245K3RILT (NEW CABIN)
	Drive mode	6*2
Engine	Model	CA6DF3-24E3F
	Emission standard	ECR
	(cc)Displacement	7120
	Max output power (Hp/rpm)	240/2300
	Max torque (N.m/rpm)	900/1300-1500
Transmission	Model	8JS105T
	Gear ratio	I、8.08 II、5.66 III、3.98 IV、2.86 V、2.05 VI、1.42 VII、1.00 VIII、0.72 RL、0.24 RH、2.07
	Gear position	RH/RL 5/1 7/3 6/2 8/4
Clutch	Mode	Single plate, dry, screw spring
Final axle	Model	gear speed rate 4.876
Main parameter	Overall dimension (mm)	11990*2496*3460
	Rear cargo dimension (mm)	8500*2300*650
	Wheelbase (mm)	1900*6400
	Tread (mm)	2040/1847
	Suspension arm (mm)	1495/2745
	Curb Weight (Kg)	14,000
	Rated payload (Kg)	12,000
	GVW (Kg)	26,000
	Max speed (Km/h)	90
Tire		11.00R20
Steering system		Power steering
Brake system	Mode	Dual-circuit air brake
Oil tank		Iron 500L
Other	Air conditional	yes
	Power window	standard
	Air seat	yes
	Spring suspension cab	yes
	Power and Manual overturn equipment	yes
Crane model	Unit	SQC260
Max Lifting Capacity	kg	12,000
Max Lifting Moment	T.M	26
Recommend Power	kw	28
Max Oil Flow of Hydraulic System	L/min	60
Max Pressure of Hydraulic System	MPa	26

